

FM52 SERIES

Digital Weighing Scale



FEATURES

- 24 Bit Sigma to Delta (Σ - Δ) Analog-To-Digital Converter
- Multi Functions Indicator
- Free Capacity and Division Setting
- 6 x 1-Inch Numeric Digits
- Tracking Bar to Show Applied & Remaining Capacity
- Calibration Password Control
- Power Up To 4 X 350 Ω Load Cells or 8 X 700 Ω Load Cells
- Dual Power Source: - By Built-In Rechargeable Battery or External Power Adaptor
- Lower Power Consumption.
Battery Operating Time = 200 Hours plus
- Built-in Real Time Clock
- Backlight, Built-In Rechargeable Battery, External Power Adaptor and Stainless Steel Wall/Desk Mount Holder Included

USER SELECTABLE PARAMETERS

- 5 x Filter Intensity Mode
- 3 x Backlight Mode
- 2 x Selectable Auto Tare Function
- 5 x RS232 Data Output Baud Rate
- 7 x Initial Zero Range
- 6 x Manual Zero Range
- 4 x Auto Zero Tracking Range
- 3 x Checkweighing Buzzer Output Mode



Accurate Weighing at Economy Price

FM52 SERIES Digital Weighing Scale

FUNCTIONS

- Weighing
- Checkweighing
- Animal Weighing
- Piece Count
- Pre-set Tare
- Memory Accumulation
- Kg/lb Conversion Function plus 2 x User Programmable Weight Units
- Auto Initial Zero Tracking
- Manual Zero

Model No.	Capacity (kg)	Readability (kg)	Platform Dimension (mm)
FM52-4252	30	5g	420 x 520mm
FM52-4252	60	10g	
FM52-4252	150	20g	
FM52-4252	300	50g	
FM52-0506	30	5g	500 x 600mm
FM52-0506	60	10g	
FM52-0506	150	20g	
FM52-0506	300	50g	
FM52-0608	60	5g	600 x 800mm
FM52-0608	150	10g	
FM52-0608	300	20g	
FM52-0608	500	50g	
Operating Environment	0~40°C (32~104°F) Non Condensing R.H. ≤85%		

Specifications subject to change prior to notice

DIMENSIONS (mm)



Fidelity Measurement Co., Ltd.
<http://www.fi-measurement.com>
e-mail: info@fi-measurement.com

REV.: FM52/11/03/00